

FTXP-L + RXP-L




Efficiency data		FTXP + RXP	20L + 20L	25L + 25L	35L + 35L	50L + 50L	60L + 60L	71L + 71L
Cooling capacity	Min./Nom./Max.	kW	1.3/2.00/2.6	1.3/2.50/3.0	1.3/3.50/4.0	1.7/5.0/6.0	1.7/6.0/7.0	2.3/7.1/7.3
Heating capacity	Min./Nom./Max.	kW	1.30/2.50/3.50	1.30/3.00/4.00	1.30/4.00/4.80	1.7/6.0/7.70	1.7/7.0/8.00	2.3/8.2/9.00
Power input	Cooling	Min./Nom./Max.	kW	0.31/0.50/0.72	0.31/0.65/0.72	0.29/1.01/1.30	0.320/1.385/1.826	0.332/1.824/2.980
	Heating	Min./Nom./Max.	kW	0.25/0.52/0.95	0.25/0.69/0.95	0.29/1.00/1.29	0.440/1.579/2.356	0.456/1.928/2.787
Space cooling	Energy efficiency class		A++					
	Capacity	Pdesign	kW	2.00	2.50	3.50	5.00	6.00
	SEER			6.79	6.92	6.62	6.72	6.82
	Annual energy consumption		kWh/a	104	127	186	261	308
Space heating (Average climate)	Energy efficiency class		A++			A+		A
	Capacity	Pdesign	kW	2.20	2.40	2.80	4.60	4.80
	SCOP/A			4.65	4.61	4.64	4.10	3.81
	Annual energy consumption		kWh/a	662	728	845	1,570	1,637
Nominal efficiency	EER			4.02	3.83	3.49	3.61	3.29
	COP			4.77	4.36	4.02	3.80	3.63
	Annual energy consumption		kWh		-		693	912
	Energy labeling Directive Cooling/Heating				A/A			-/-

Indoor unit		FTXP	20L	25L	35L	50L	60L	71L
Dimensions	Unit HeightxWidthxDepth	mm	286x770x225			295x990x263		
Weight	Unit	kg	9.00			13.5		
Air filter	Type		Removable / washable					
Fan	Air flow rate	Cooling	4.4/5.9/7.9 / 9.8	4.4/6.1/8.1 / 10.1	4.5/6.3/8.3 / 11.5	10.5/11.9/14.4 / 16.8	10.7/12.2/14.8 / 17.3	
		Heating	5.3/6.5/8.4 / 10.3	5.3/6.7/8.6 / 10.3	5.3/7.0/9.0 / 11.5	10.7/12.2/14.8 / 17.3	11.3/12.8/15.8 / 17.9	
Sound power level	Cooling	dBA	55		58	59	60	62
	Heating	dBA	55		58	61	62	
Sound pressure level	Cooling	Silent operation/Low/High	dBA	20/25/39	20/26/40	20/27/43	31/34/43	33/36/45
	Heating	Silent operation/Low/High	dBA	21/28/39	21/28/40	21/29/40	30/33/42	32/35/44
Control systems	Infrared remote control		ARC480A11					
	Wired remote control		BRC944B2 / BRC073A1			BRC073A1		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240					

Outdoor unit		RXP	20L	25L	35L	50L	60L	71L
Dimensions	Unit HeightxWidthxDepth	mm	550x658x275			734x870x373		
Weight	Unit	kg	28			46.0	50.0	
Sound power level	Cooling	dBA	60		62	61	63	66
	Heating	dBA	61		62	61	63	65
Sound pressure level	Cooling	Nom./High	dBA	-/46		-/48	47/-	49/-
	Heating	Nom./High	dBA	-/47		-/48	49/-	52/-
Operation range	Cooling	Ambient	Min.-Max.	-10~-46				
	Heating	Ambient	Min.-Max.	-15~-18			-15~-18	
Refrigerant	Type		R-32					
	GWP		675.0					
	Charge	kg/CO ₂ Eq	0.70/0.48			0.90/0.61	1.15/0.78	
Piping connections	Liquid	OD	6,35			6,4		
	Gas	OD	9,5			12,7		
	Piping length	OU - IU	Max. 15			30		
	Additional refrigerant charge	kg/m	0.02 (for piping length exceeding 10m)					
	Level difference	IU - OU	Max. 12			20		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240					
Current - 50Hz	Maximum fuse amps (MFA)	A	-			16		

Daikin Europe N.V. Naamloze Vennootschap Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN18 - 046A 03/18



Daikin Europe N.V. participates in the Eurovent Certified Performance programme for Liquid Chilling Packages and Hydronic Heat Pumps, Fan Coil Units and Variable Refrigerant Flow systems. Check ongoing validity of certificate: www.eurovent-certification.com



The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this publication to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.

Printed on non-chlorinated paper.