


Concealed floor standing unit

Designed to be concealed in walls

- › Discretely concealed in the wall: only the suction and discharge grilles are visible
- › Requires very little installation space as the depth is only 200mm



- › Its low height (620 mm) enables the unit to fit perfectly beneath a window
- › High ESP allows flexible installation

 Access all technical information on FXNQ-A at my.daikin.eu or [click here](#)

Indoor unit			FXNQ	20A	25A	32A	40A	50A	63A
Cooling capacity	Total capacity	Nom.	kW	2.20	2.80	3.60	4.50	5.60	7.10
Heating capacity	Total capacity	Nom.	kW	2.50	3.20	4.00	5.00	6.30	8.00
Power input - 50Hz	Cooling	Nom.	kW	0.071			0.078	0.099	0.110
	Heating	Nom.	kW	0.068			0.075	0.096	0.107
Dimensions	Unit	HeightxWidthxDepth	mm	620 / 720x790x200			620 / 720x990x200		620 / 720x1,190x200
Weight	Unit		kg	23.5			27.5		32.0
Casing	Material			Galvanised steel plate					
Fan	Air flow rate - 50Hz	Cooling	Low/High	6.4/8.0			8.5/10.5	10.0/12.5	13.0/16.5
		Heating	Low/High	6.4/8.0			8.5/10.5	10.0/12.5	13.0/16.5
	External static pressure - 50Hz	Nom./High	Pa	10/41.0		10/42.0	15/52.0	15/59.0	15/55.0
Air filter	Type			Resin net					
Sound power level	Cooling	High	dBA	51			52	53	54
	Sound pressure level	Cooling	Low/Nom./High	dBA	27.0/28.5/30.0			28.0/30.0/32.0	29.0/31.0/33.0
		Heating	Low/Nom./High	dBA	27.0/28.5/30.0			28.0/30.0/32.0	29.0/31.0/33.0
Refrigerant	Type/GWP			R-410A/2,087.5					
Piping connections	Liquid	OD	mm	6.35					9.52
	Gas	OD	mm	12.7					15.9
	Drain			VP20 (I.D. 20/O.D. 26)					
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50/60/220-240/220					
Current - 50Hz	Maximum fuse amps (MFA)		A	16					
Control systems	Infrared remote control			BRC4C65					
	Wired remote control			BRC1D52 / BRC1E53A/B/C / BRC1H519W/S/K					