


4-way blow ceiling suspended unit

Unique Daikin unit for high rooms with no false ceilings nor free floor space


- › Even rooms with ceilings up to 3.5m can be heated up or cooled down very easily without capacity loss
- › Can easily be installed in both new and refurbishment projects
- › Individual flap control: flexibility to suit every room layout without changing the location of the unit!




- › Stylish unit blends easily with any interior. The flaps close entirely when the unit is not operating and there are no air intake grilles visible
- › Optimum comfort guaranteed with automatic air flow adjustment to the required load
- › 5 different discharge angles between 0 and 60° can be programmed via the remote control



- › Standard drain pump with 500mm lift increases flexibility and installation speed



 Access all technical information on FXUQ-A at my.daikin.eu or click here

Indoor unit		FXUQ		71A	100A
Cooling capacity	Total capacity	Nom.	kW	8.0	11.2
Heating capacity	Total capacity	Nom.	kW	9.0	12.5
Power input - 50Hz	Cooling	Nom.	kW	0.090	0.200
	Heating	Nom.	kW	0.073	0.179
Dimensions	Unit	HeightxWidthxDepth		198x950x950	
Weight	Unit	kg		26	27
Casing	Material		Resin		
Fan	Air flow rate - 50Hz	Cooling	Low/High	16.0/22.5	
		Heating	Low/High	16.0/22.5	
Air filter	Type		Resin net with mold resistance		
Sound power level	Cooling	Nom./High		56/58	
	Sound pressure level	Cooling	Low/Nom./High	36.0/38.0/40.0	
	Heating	Low/Nom./High		36.0/38.0/40.0	
		Heating	Low/Nom./High	36.0/38.0/40.0	
Refrigerant	Type/GWP		R-410A/2,087.5		
Piping connections	Liquid	OD	mm	9.52	
	Gas	OD	mm	15.9	
	Drain			I.D. 20/O.D. 26	
Power supply	Phase/Frequency/Voltage		Hz/V 1~/50/60/220-240/220-230		
Current - 50Hz	Maximum fuse amps (MFA)		A 16		
Control systems	Infrared remote control		BRC7C58		
	Wired remote control		BRC1H519W/S/K / BRC1E53A/B/C / BRC1D52		