


# Wall mounted unit

For rooms with no false ceilings nor free floor space

- › Flat, stylish front panel blends easily within any interior décor and is easier to clean
- › Can easily be installed in both new and refurbishment projects
- › The air is comfortably spread up- and downwards thanks to 5 different discharge angles that can be programmed via the remote control
- › Maintenance operations can be performed easily from the front of the unit



 Access all technical information on FXAQ-A at [my.daikin.eu](http://my.daikin.eu) or click here

Indoor unit				FXAQ	15A	20A	25A	32A	40A	50A	63A
Cooling capacity	Total capacity	Nom.	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1	
	Heating capacity	Total capacity	Nom.	1.9	2.5	3.2	4.0	5.0	6.3	8.0	
Power input - 50Hz	Cooling	Nom.	kW	0.02		0.03		0.02	0.03	0.05	
	Heating	Nom.	kW	0.03		0.04	0.02	0.04	0.06		
Dimensions	Unit	HeightxWidthxDepth		290x795x266				290x1,050x269			
Weight	Unit			12				15			
Fan	Air flow rate - 50Hz	Cooling	Low/High	m <sup>3</sup> /min	7.0/8.4	7.0/9.1	7.0/9.4	7.0/9.8	9.7/12.2	11.5/14.4	13.5/18.3
			High								
Air filter	Type			Washable resin net							
Sound power level	Cooling	High	dBA	51.0	52.0	53.0	55.0	58.0	63.0		
Sound pressure level	Cooling	Low/High	dBA	28.5/32.0	28.5/33.0	28.5/35.0	28.5/37.5	33.5/37.0	35.5/41.0	38.5/46.5	
	Heating	Low/High	dBA	28.5/33.0	28.5/34.0	28.5/36.0	28.5/38.5	33.5/38.0	35.5/42.0	38.5/47.0	
Refrigerant	Type/GWP			R-410A/2,087.5							
Piping connections	Liquid	OD	mm	6.35				9.52			
	Gas	OD	mm	12.7				15.9			
	Drain			VP13 (I.D. 15/O.D. 18)							
Power supply	Phase/Frequency/Voltage			1~/50/220-240							
Current - 50Hz	Maximum fuse amps (MFA)			16							
Control systems	Infrared remote control			BRC7EA628 / BRC7EA629							
	Wired remote control			BRC1H519W/S/K / BRC1E53A/B/C / BRC1D52							